

Wet Chop Strands 8007

Product Description

Wet Chop Strands 8007 are manufactured in the EU by Nippon Electric Glass, are produced from a continuous filament strand and are designed for quick and easy dispersion in gypsum feeder systems. As a premier wet chop product for gypsum applications, The 8007 wet chop fiber glass is easy to process and offers excellent performance in the end-use application. It provides outstanding characteristics such as flow consistency, fiber dispersion and fiber distribution in end end-use applications. The 8007 wet chop fiberglass is designed for reinforcement of gypsum products.

User Benefits

- Aqueous-based sizing optimizes for fiber dispersion.
- Supported by NEG's technical resources.
- Manufactured and available in the Europe.
- Manufacturing facilities operate quality management systems that comply with ISO 9001:2015 requirements.

Type of Fiber	E-Glass (ASTM D 578-05)
Type of Sizing	Silane
Nominal Fiber Diameter (µm)	16
Nominal LOI (%)	EU: 0.15
Nominal Moisture Content (%)	7.5
Nominal Chop Length (mm)	EU: 12

Packaging

- 1,000 kg / 1,100 kg bigbags (dry weight)
- 20 kg PE bags (dry weight)

Storage

These products should be stored in a cool and dry area. Protect product from all sources of water at all times. A First-in-First-Out (FIFO) stock control system is recommended to minimize the influence of storage conditions. Prior to use, products should be conditioned in the work area for a minimum of 24 hours. If contents of a package unit are partially used, the unit should be closed until the next use. To insure optimal performance, retesting is recommended for products stored more than one year from the original production date.

More Information

<https://www.neg.co.jp/inquiry/>

<https://www.neg.co.jp/en/inquiry/>